



# KIP-2030F



IP BOX 2.0 Mega Pixel

High Definition 1080P

Support ONVIF2.4 protocol

3MP HD Lens Fixed 3.6mm, IR up to 30 meters, IP66 Outdoor

## SPECIFICATIONS

<b>Image Device</b>	1/ 2.7" 2.0 Mega Pixels HD CMOS Sensor
<b>ONVIF</b>	Support ONVIF 2.4
<b>Effective Pixels</b>	2.0 Mega Pixel
<b>Maximum resolution</b>	1920*1080@25fps
<b>Electronic Shutter Time</b>	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
<b>S/N Ratio</b>	≥52dB
<b>Lens Focal Length</b>	3M Pixels / Board Lens 3.6mm/F2.0
<b>Infrared LED</b>	36 pcs* ϕ 5mm IR LED
<b>Infrared Distance</b>	30M
<b>IR Status</b>	Under 10 Lux by CDS
<b>Ethernet</b>	RJ-45
<b>Protocol</b>	TCP/IP, UDP, RTSP, DNS, DDNS, DHCP, FTP, NTP, SMTP, UPNP
<b>P2P</b>	YES
<b>POE</b>	Optional
<b>Video Bit-rate</b>	32Kbps~16Mbps, Supports CBR/VBR ;
<b>Main Stream</b>	1920*1080,1-25(30)
<b>Remote Monitoring</b>	IE Browsing、CMS remote control
<b>Smart Phone</b>	iPhone, iPad, Android, Android Pad
<b>Compression</b>	H.264/JPEG
<b>Day/Night</b>	Color/ B&W (IR-CUT )
<b>WDR</b>	YES
<b>Recording Mode</b>	NVR/NAS/CMS/Web
<b>IR Cut Filter</b>	YES
<b>Housing</b>	Metal,IP 66
<b>Operation Temperature</b>	-10°C ~ +50°C RH95% Max
<b>Storage Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Power Source</b>	DC12V±10%, 500mA
<b>Certification</b>	CE, FCC, RoHS