



KIP-400SLP



4MP IR Fixed-focal Bullet
High Definition 1440 Pixels
1/2.7" illumination Smart Sensor
H.265 Lens Fixed 3.6mm , IR up to 30 meters, IP66 Outdoor

SPECIFICATIONS

Image Sensor	1/2.7" Smart illumination CDS Sensor
Image Resolution	HP 4 Mega Pixel 1440P
Effective Pixels	2560*1440 (25fps)
TV System	PAL/NTSC
Electronic Shutter Time	1/25-1/10000Sec, 1/25-1/10000Sec
S/N Ratio	≥52dB (0.0001 Lux@F1.6)
Scanning System	Progressive Scan
Manual Lens	3.6mm
Min Illumination	0.01 Lux
Infrared LED	3015U×4 PCS, Warm white (4000K)
Infrared Distance	30M
IR Power On	CDS Auto Control
Day/Night	Color / B&W (IR-Cut)
ONVIF	Support ONVIF 2.4
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP, FTP, PPPOE, DHCP, DDNS, NTP, UPnP etc.
IE Brower	Google Chrome (IE TAB), Firefox (IE TAB), IE-6-11
Image Config	Saturation/Brightness/Contrast/ Sharpness, Mirror
WDR, BLC, Motion Detection	Yes
Recording Mode	NVR/NAS/CMS/Web
Anit-cut Bracket	Yes, Anti-Cut Bracket
Dual Voltage	DC 12V
IR Cut Filter	Yes
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 700mA PoE (802.3af, 36V to 57V)
Dimension	Size: 175(W) x 69(H) x55(D)mm
Certification	CE, FCC, RoHS