



KIP-200SA



IP BOX 2.0 Mega Pixel

High Definition 1080 Pixels

1/2.8" Sony illumination Sony Sensor ,Built-in Audio

H.265+ Lens Fixed 3.6mm 3M Pixels, IR up to 30 meters, IP66

SPECIFICATIONS

Image Sensor	1/2.8" Star-Light illumination Sony Sensor
Image Resolution	2 MP 1080P
Effective Pixels	1920*1080
TV System	PAL/NTSC
Electronic Shutter Time	1/25-1/10000Sec , 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive Scan
Manual Lens	3.6mm
Pixels Lens	Star level 3 MP Pixels
Min Illumination	0.001 Lux
Infrared LED	ø12x36PCS
Infrared Distance	30M
IR Power On	CDS Auto Control
Day/Night	Color / B&W (IR-Cut)
ONVIF	Support ONVIF 2.4
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,FTP,DHCP,DNS,DDNS,RTP,RTSP,NTP,SMTP
IE Brower	IE8-11,Google Chrome, Firefox, Safari, Mac Safari
Image Config	Saturation/Brightness/Contrast/Sharpness,Mirror,3D NR, White Balance, FLK(Flicker Control)
WDR, BLC, Motion Detection	Yes
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR /UC (Option, VMS) /Web
Housing	Metal ,IP66
Dual Voltage	DC 12V
IR Cut Filter	Yes
Operation Temperature	-30°C ~ +60°C RH95% Max
Storage Temperature	-40°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 600mA
Dimension	Size : 200(W) x70(H) x65(D)mm
Certification	CE, FCC, RoHS