



NVR-1116



Features:

- Support VGA, HDMI full HD output simultaneously;
- Support ONVIF, Access third party;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.);

SPECIFICATIONS

Model	NVR-1116	
System	Main processor	Hi3536D
	Operating system	Embedded LINUX operating system
	System resource	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operation interface	16 bit real color GUI interface support mouse operation
	Preview	1/4/8/16
Video	Video input (IP)	16*5M@15fps / 8*5M / 16*1080P
	Access bandwidth	64Mbps
	Forwarding bandwidth	36Mbps
	Video compression	H.265AI/H.265+ (Compatible with H.265/H.264)
	Display quality	Max 2560*1440
	Playback quality	5M/1080P
	Decode	1*5M / 2*1080P
	Human shape / Face	Support(depend on camera)
Audio	Audio compression	G.711A
	Intercom	unsupported
Record and Playback	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Local playback	1*5M / 2*1080P
	Search mode	Search by Time/Calendar/Event/Channel
	Record storage	HDD, Network
	Back up mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch VGA, 1ch HDMI HD output
	Audio I/O	0/1 (3.5mm audio output)
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100MAdaptive Ethernet port
	USB interface	2*USB2.0 ports
	HDD	1 SATA(Up to 8TB for each disk)
User	User level	Admin / User
	Password protection	Yes
General	PTZ control	Control PTZ device by network
	ONVIF	Support
	Power supply	12V/2A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0°C- +55°C , Humidity:10% –90%RH , Atm:86kpa – 106kp
	Dimension	260mm*43mm*190mm