



NVR-1108



Features:

- Support VGA, HDMI full HD output simultaneously;
- Support ONVIF, Access third party;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.);

SPECIFICATIONS

| | | |
|---------------------|----------------------|---|
| Model | NVR-1116 | |
| System | Main processor | Hi3536D |
| | Operating system | Embedded LINUX operating system |
| | System resource | Simultaneous multi-channel real-time recording, playback, network operation, USB backup |
| Interface | Operation interface | 16 bit real color GUI interface support mouse operation |
| | Preview | 1/4/8 |
| Video | Video input (IP) | 8*5M / 4*5M |
| | Access bandwidth | 64Mbps |
| | Forwarding bandwidth | 36Mbps |
| | Video compression | H.265AI/H.265+ (Compatible with H.265/H.264) |
| | Display quality | Max 2560*1440 |
| | Playback quality | 5M |
| | Decode | 1*5M |
| Audio | Human shape / Face | Support(depend on camera) |
| | Audio compression | G.711A |
| | Intercom | unsupported |
| Record and Playback | Recording mode | Manual>Alarm>Dynamic Detection>Timing |
| | Local playback | 1*5M |
| | Search mode | Search by Time/Calendar/Event/Channel |
| | Record storage | HDD, Network |
| | Back up mode | Network backup, USB hard disk, USB burner, SATA burner |
| External interface | Video output | 1ch VGA, 1ch HDMI HD output |
| | Audio I/O | 0/1 (3.5mm audio output) |
| | Alarm I/O | 0/0 |
| | Network interface | The expansion board provides a network connection |
| | USB interface | 2*USB2.0 ports |
| | HDD | 1 SATA(Up to 8TB for each disk) |
| User | User level | Admin / User |
| | Password protection | Yes |
| General | PTZ control | Control PTZ device by network |
| | ONVIF | Support |
| | Power supply | 12V/2A |
| | Power Consumption | <10W(Without HDD) |
| | Work environment | Temperature:0°C- +55°C , Humidity:10% –90%RH , Atm:86kpa – 106kp |
| | Dimension | 260mm*43mm*190mm |