



KIP-2000S



IP BOX 2.0 Mega Pixel
High Definition 1080P

1/2.8" Star-Light illumination CMOS Sensor

H.265 Lens Fixed 3.6mm, IR up to 30 meters, IP66 Outdoor

SPECIFICATIONS

Image Device	1/ 2.8" Star-Light illumination 2.0 Mega Pixels HD CMOS Sensor
ONVIF	Support ONVIF 2.4
Effective Pixels	2.0 Mega Pixel
Maximum resolution	1920*1080@25fps
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥50dB
Lens Focal Length	3M Pixels / Board Lens 3.6mm/F2.0
Infrared LED	36 pcs* ϕ 5mm IR LED
Infrared Distance	30M
IR Status	Under 10 Lux by CDS (IR Power on auto control)
Ethernet	RJ-45
Protocol	TCP/IP, UDP, RTSP, DNS, DDNS, DHCP, FTP, NTP, SMTP, UPNP
P2P	YES, Support QR Code
POE	Optional
Video Bit-rate	32Kbps~16Mbps, Supports CBR/VBR ; Main stream: 1920*1080@25fps, 1280*720@25fps; sub-stream: 704*576@25fps
Image output	
Remote Monitoring	IE8-11, Google Chrome, Firefox, Safari, Mac Safari, CMS
Smart Phone	iPhone, iPad, Android, Android Pad
Compression	H.265/H.264/JPEG/AVI
Day/Night	Color/ B&W (IR-CUT)
Noise Reduction	Support 2D/3D
Recording Mode	NVR/NAS/CMS/Web
IR Cut Filter	YES
Housing	Metal, IP 66
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 800mA
Certification	CE, FCC, RoHS