



# NVR-8132



## Features:

- Support VGA, HDMI full HD output simultaneously;
- Support ONVIF, Access third party;
- Support web, CMS, center platform management
- Software MYEYE, provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;

## SPECIFICATIONS

Model	NVR-8132	
System	Main processor	Hi3536C
	Operating system	Embedded LINUX operating system
	System resource	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operation interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4/9/16/32
Video	Video input (IP)	32*5M/8*4K/32*1080P
	Video standards	PAL(625TVL,50f/s); NTSC(525TVL,60f/s)
	Video compression	H.265/H.264
	Display quality	Max:4K
	Playback quality	5M/4K/1080P
	Decode	2*5M/1*4K/4*1080P
Audio	Motion detection	Depend on camera
	Audio compression	G.711A
	Intercom	supported
Record and Playback	Recording mode	Manual>Alarm>Video Detection>Continuous
	Local playback	2*5M/1*4K/4*1080P
	Search mode	Search by Time/calendar/event/channel
	Record storage	HDD, Network
	Back up mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch VGA, 1ch HDMI HD output
	Audio I/O	1/1
	Alarm I/O	No
	Network interface	1*RJ45 10M/100M /1000M Adaptive Ethernet port
	USB interface	1*USB2.0 port,1*USB3.0 port (Reserved 2 pre interface)
	HDD	2*SATA(Up to 8TB for each disk)
User	User level	Admin / User
	Password protection	Yes
General	PTZ control	Control PTZ device by network
	ONVIF	Support
	Power supply	12V/6A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0°C-+55°C , Humidity:10%—90%RH , Atm:86kpa—106kp
	Dimension	310mm*43mm*20mm
	Weight	4KG/PCS