



# NVR-1108



## Feature:

- Support H.265+ encoding, ultra-low bitrates, compatible with H.264 surroundings;
- Support VGA, HDMI full HD output simultaneously;
- Support ONVIF; access third party;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support web, VMS, center platform management software MYEYE, provide SDK development;
- Support various mobile monitoring (iPhone, Android);

## SPECIFICATIONS

Model		NVR-1108
System	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Preview	1/4/8/9/16
	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
Video	Video input (IP)	10*4K
	Video compression	H.265A/H.265+(compatible H.265/H.264)
	Display quality	Max:4K
	Playback quality	4K/5M/4M/3M/1080P
	Decode	4K (1) /5M (1+1) /4M (2+1)/3M (2+2) /1080P (4+1)
	human shape / Face	Support (depend on camera)
Audio	Audio compression	G.711A
	Intercom	support
Record& playback	Record mode	manual>alarm>motion detection>timing
	Local payback (Real-time/nonreal-time)	4K (1) /5M (1+1) /4M (2+1)/3M (2+2) /1080P (4+1) 16ch (analog input mode)
	Search mode	Search by Time/Calendar/Event/Channel/Face
Storage& backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	1ch VGA, 1ch HDMI HD output
	Audio I/O	1/1 (3.5mm)
	Alarm I/O	0 (Can be extended to 4ch) /0 (Can be extended to 1ch)
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port
	PTZ control	1*RS485, Support kinds of PTZ protocols
	USB	2*USB2.0 ports (one USB extension interface is reserved)
	HDD	1* SATA (Up to 14TB for each disk)
	Wireless	3G, WIFI (extend via USB)
General	ONVIF	Support
	Power Consumption	<10W (Without HDD)
	Working environment	Temperature:0°C – 55°C, Humidity:10% – 90%RH, Atm:86kpa – 106kp
	Dimension	250mm*212mm*42mm
	Weight	2KG
	Power supply	12V/5A