



# KIP-300SLP



IP BOX 3.0 Mega Pixel PoE

High Definition 1536 Pixels

1/2.8" illumination CDS Sensor

H.265+ Lens Fixed 3.6mm 3M Pixels, IR up to 30 meters, IP66

## SPECIFICATIONS

<b>Image Sensor</b>	1/2.8" Star-Light illumination CDS Sensor
<b>Image Resolution</b>	3 MP 1536P
<b>Effective Pixels</b>	2048*1536 (25FPS)
<b>TV System</b>	PAL/NTSC
<b>Electronic Shutter Time</b>	1/25-1/10000Sec , 1/25-1/10000Sec
<b>S/N Ratio</b>	≥52dB (0.0001 Lux@F1.6)
<b>Scanning System</b>	Progressive Scan
<b>Manual Lens</b>	3.6mm
<b>Pixels Lens</b>	Star level 3 MP Pixels
<b>Min Illumination</b>	0.0001 Lux
<b>Infrared LED</b>	ø12x36PCS
<b>Infrared Distance</b>	30M
<b>IR Power On</b>	CDS Auto Control
<b>Day/Night</b>	Color / B&W (IR-Cut)
<b>ONVIF</b>	Support ONVIF 2.4
<b>Ethernet</b>	RJ45 (10/100Base-T)
<b>Protocol</b>	TCP/IP,ICMP,HTTP,FTP,DHCP,DNS,DDNS,RTP,RTSP,NTP,SMTP
<b>IE Brower</b>	IE8-11,Google Chrome, Firefox, Safari, Mac Safari
<b>Image Config</b>	Saturation/Brightness/Contrast/Sharpness,Mirror,3D NR, White Balance, FLK(Flicker Control)
<b>WDR, BLC, Motion Detection</b>	Yes
<b>Privacy Masking</b>	3 Rectangular Zone
<b>Recording Mode</b>	NVR /UC (Option, VMS) /Web
<b>Housing</b>	Metal ,IP66
<b>Dual Voltage</b>	DC 12V
<b>IR Cut Filter</b>	Yes
<b>Operation Temperature</b>	-30°C ~ +60°C RH95% Max
<b>Storage Temperature</b>	-40°C ~ +60°C RH95% Max
<b>Power Source</b>	DC12V±10%, 600mA PoE (802.3af, 36V to 57V)
<b>Dimension</b>	Size : 200(W) x70(H) x65(D)mm
<b>Certification</b>	CE, FCC, RoHS