



XVR-3216



Feature:

- Support H.265+ encoding, ultra-low bitrates, compatible with H.264 surroundings;
- Support VGA, HDMI full HD output simultaneously; Support CVBS output
- Support ONVIF; access third party;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support web, VMS, center platform management software MYEYE, provide SDK development;
- Support various mobile monitoring (iPhone, Android);
- Support UTC, control signal& video stream transmit through one single coaxial
- Support XVI/AHD/TVI/CVI/CVBS/IP six signals;

SPECIFICATIONS

Model		XVR-3216
System	Main processor	NT98312
Interface	Preview	1/4/8/9/16
	Codec	H.265, H.265+
	Monitor quality	VGA (1080P at most) ; HDMI (4K at most); CVBS
Video	Preview ability	16*5M-N@12fps (6 in 1)/16*4M-N@15fps (6 in 1)/16*1080P@15fps (XVI), default 5M-N
	Encode ability	16*5M-N@6fps (6 in 1)/16*4M-N@8fps (6 in 1)/16*1080P@8fps (XVI) , default 5M-N
	Decode ability	8*5M-N@6fps (6 in 1)/16*4M-N@8fps (6 in 1)/16*1080P@8fps (XVI) , default 5M-N
	Multi-mode input	Analog: 16*5M-N hybrid: 16*5M-N (analog) +4*1080P (network) network: 16*1080P; 4*5M
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
	Intercom	support
Record& playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	16ch (analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage& backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	16ch BNC
	Video output	1ch HDMI
	Audio I/O	2 (Can be extended to 6ch) /1
	Alarm I/O	0 (Can be extended to 4ch) /0 (Can be extended to 1ch)
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	1*RS485, Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	2*SATA ports (Maximum support 14T)
	Wireless	3G, WIFI (extend via USB)
General	Power supply	12V/2A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0°C—+55°C, Humidity:10%—90%, Atm:86kpa—106kpa
	Dimension	262*43*192MM
	Weight	2KG
	Power supply	12V/5A