



## IPC-1013

### Feature

- \* 1/3" Progressive Scan CMOS
- \* Up to 1.3MP resolution, real-time image,
- \* Low illumination, 0.1Lux @ (F1.2, AGC ON), 0 LUX with IR
- \* H.264 main profile compression
- \* Support IR-CUT filter switch to achieve day and night monitoring
- \* Support motion detection and sending mail alert automatically
- \* Support smart mobile and network Surveillance
- \* Support network user management,
- \* Compatible with ONVIF standard
- \* Support real-time remote monitoring, playback and downloading;

## Specification

|                         |   |
|-------------------------|---|
| Model                   | IPC-1013  |
| <b>Camera</b>           |   |
| Image Sensor            | 1/3" Progressive Scan CMOS  |
| Signal System           | PAL/NTSC  |
| Effective Resolution    | 1920×960  |
| Min. Illumination       | Color:0.1Lux @ (F1.2,AGC ON),0 LUX with IR                            |
| Electronic Shutter      | 1/50(1/60)s - 1/100,000 s   |
| Lens                    | 4mm lens  |
| Day & Night             | Support IR-CUT  |
| IR Distance             | 1PCS Array LED, 40Meter IR Distance                                   |
| Synchronization way     | Internal synchronization  |
| Video Output            | 1Vp-p Composite Output(75Ω/BNC)                                       |
| S/N Ratio               | > 48dB  |
| <b>Compression</b>      |   |
| Video Compression       | H.264 Main Profile, JPEG Capture                                      |
| Video Bite Rate         | 32 Kbps~8Mbps   |
| <b>Image</b>            |   |
| Max. Resolution         | 1920*1080   |
| Frame Rate              | 50Hz:25fps (1920*960)   |
|                         | 60Hz:30fps (1920*960)   |
| <b>Network Function</b> |   |
| Storage                 | Support network storage   |
| Intelligent Alarm       | Motion detect, Video loss, Network disconnection, IP address conflict |
| Protocols               | TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE, SMTP,NTP                            |
|                         | (HTTPS,SIP ,802.1x,IPv6 Optional)                                     |
| Basic                   | Anti-flicker, Dual stream, Heartbeat, Password protection             |
| <b>Interface</b>        |   |
| Communication Interface | 1 RJ45 10M/100M self-adaptive Ethernet interface                      |
| Video Output            | 1Vp-p Composite Output(75Ω/BNC)                                       |
| <b>General</b>          |   |
| Operating Condition     | -10℃~60℃,Humidity 90% or less(non-condensing)                         |
| Power Supply            | DC12V±10%   |