



HD IP CAMERA



Solution	KIP-3120
Description	HI 1.3MP IP camera
Sensor type	1/3" 1.37 Megapixel CMOS Image sensor Sony IMX238
Minimum Illumination	0.01Lux
S/N Ratio	>50db
Shutter	1—1/10000s(adjustable)
Lens	2.8mm/3.6mm/4mm/6mm/8mm/2.8-12mm(adjustable),Lens optional
Lens interface type	C/CS
Day/Night	ICR-infrared filter
Video Compression	H.264/JPEG
Bit Rate	64-12000Kbps
Max image size	1280×960
Frame Rate	50Hz:25fps(1280×960) 60Hz:30fps(1280×960)
Image setting	Brightness, contrast, saturation, sharpness can be adjusted
Backlight Compensation	Support
Storage function	FTP、 Local、 NVR、 SMTP
Onvif	Onvif 2.4(port:8999)
Intelligent alarm	Motion detection、 Privacy
Protocol	TCP/IP、 HTTP、 DHCP、 FTP、 DNS、 DDNS、 RTSP、 NTP、 SMTP
General function	Tri-Stream/Mirror
Communication interface	RJ45 (10M/100M) Adaptive Ethernet port
Temperature	-20 ~ 55°C
Humidity	0%-90%RH Without Condensation
Power	DC12V±5% / PoE(802.3af)
Size	38×38mm